



d ₁	M1,6	M2	M2,5	M3	(M3,5)	M4	M5	M6	M8	M10
d ₂ max.	3,2	4	5	6	7	8	10	12	16	20
k max.	1,42	1,72	2,12	2,52	2,82	3,25	3,95	4,75	6,15	7,68
 Phillips	0	1	1	1	2	2	2	3	4	4
m~	1,8	2,5	2,7	3,1	4,2	4,6	5,3	6,8	9	10,2
t	min.	0,72	1,1	1,3	1,7	1,74	2,04	2,77	4,18	5,38
	max.	1,02	1,4	1,6	2	2,24	2,54	3,27	4,68	5,88
Charge d'épr. en N	370	600	990	1560	2100	2720	4400	6230	11400	18000
Proof load N										

d ₁	M2	M2,5	M3	M4	M5	M6
d ₂ max.	4	5	6	8	10	12
k max.	1,72	2,12	2,52	3,25	3,95	4,75
 Pozidriv	1	1	1	2	2	3
m~	2,4	2,6	3	4,3	5	6,7
t	min.	1,1	1,27	1,68	1,9	2,64
	max.	1,35	1,52	1,93	2,36	3,1
Charge d'épr. en N	600	990	1560	2720	4400	6230
Proof load N						

